



UF-5000

Fully automated urine flow cytometer



What's in it for you?

Sensitive and fast urinary sediment analysis

Rely on thousands of particles counted and classified from your native urine samples

Body fluid analysis always on board

Accelerate and standardise analysis of your most delicate samples

high counting reliability

■ Powerful blue (488 nm) laser

■ Two different analysis channels

Superior differentiation of particles:

All particles are analysed by multiple signals

■ Depolarised side scattered (DSS) light signal

Fast, precise and accurate analysis



Substantial diagnostic information

- Quantitative, highly sensitive and specific bacteria count incl. differentiation according to Gram-stain behaviour; helps decrease bacterial antibiotic resistance
- Differentiation of epithelial cells and casts direct counts for squamous, non-squamous, transitional and renal tubular epithelial cells, as well as hyaline and pathological casts
- Marked discrimination between red blood cells and crystals by the new DSS signal

Valuable body fluid analysis

- Quantitative bacteria determination delivers immediate answers for bacterial infections
- White blood cell differentiation into mononuclear and polymorphonuclear cells find the root cause of infections faster



Intelligent data management with U-WAM

- Clear reagent status indication and result display on one screen
- Rule-based workflow management and result interpretation



State-of-the-art reagent and QC management

- Stay on the safe side with our SNCS network daily external QC without any additional measurement
- New cartridge system with RFID labels makes changing reagents safe and easy



Key benefits

Modular and scalable

- Automate your urinalysis workflow by adding the components you need: UC-3500 and/or UD-10, all controlled by U-WAM
- Multiply your throughput by connecting more than one UF-5000 together

Superior diagnostics

- Superb differentiation of urine particles
- Up to 27 parameters per urine sample
- Know about UTI in less than a minute

Powerful body fluid analysis

- Available 24/7 by the switch of a button
- No sample pre-treatment necessary
- Nine parameters incl. bacteria count and WBC differentiation



Key specifications

Technologies fluorescence flow cytometry with blue semi-conductor laser

and hydrodynamic focussing in two different channels

conductometry

Parameters

RBC, NL RBC, WBC, WBC Clumps, EC, Squa.EC, Non SEC, Tran.EC, RTEC, CAST, Hy.CAST, Path.CAST, Urine

BACT, X'TAL, YLC, SPERM, MUCUS, Lysed RBC, SRC, DEBRIS, conductivity, osmolality, ...

Flags: RBC-Info, BACT-Info, UTI-Info

Body fluid RBC, WBC, MN#, MN%, PMN#, PMN%, EC, TNC, BACT

Throughput urine: max. 105 samples / hour

body fluid: max. 20 samples / hour

Sampling volume sampler mode (urine): 2 mL

STAT mode (urine/body fluid): o.6 mL

Aspiration volume 450 µL in all modes

Sampler unit capacity integrated stand-alone sampler: 50 samples/loading area; 70 samples/exit area

modular sampler: 80 samples/each area

Data management U-WAM (Urinalysis Work Area Information Management System) **Options**

connection of UC-3500 and/or UF-5000/4000 and/or UD-10 wagon(s), rack entry and rack exit units

Dimensions / weights main unit incl. sampler: W x H x D [mm/kg] approx. 760 x 855 x 754 / 90

Design and specifications may be subject to change due to further product development. Changes are confirmed by their appearance on a newer document and verification according to its date of issue.

© Copyright 2016 - Sysmex Europe GmbH

Authorised representative: Sysmex Europe GmbH
Bornbarch 1, 22848 Norderstedt, Germany · Phone +49 40 52726-0 · Fax +49 40 52726-100 · info@sysmex-europe.com · www.sysmex-europe.com